

LEADER TECHNOLOGIES CO.,LTD

http://www.sino-leader.com/ email: sales@sino-leader.com/ Tel: 0086-21-61317292 Fax:0086-21-61566126

Technical Data Sheet

Rubber Adhesive RA-65

04/07/2015

CAS No.: 3089-11-0

Chemical Name:

Hexamethoxymethylmelamine (HMMM) 65% + inert carrier (white carbon black).

It is similar to CYREZ® 964

Technical Specification:

Item		Technical Specifications
Appearance		White powder
Ash content (850°C)	%	29~35
Water content	% ≤	4.50
Sieve residue	% ≤	0.30
Free formaldehyde content	% ≤	0.10
Active ingredient	% >	65
Heating Loss	% ≤	4.5

Properties: Rubber adhesive RA-65 is methylene donor in bonding system for rubber and

steel cord or fabric cord. It can promote adhesion between rubber and steel cord or

fabric cord.

Application: Suggested ratio:

2-5phr Rubber adhesive RA-65 with 2-5phr resorcinol formaldehyde resin.

Package: In woven bag or paper bag lined with PE film bag, net weight: 25Kg/bag.

Storage: Stored at room temperature.

Precaution: Please refer to the appropriate material safety data sheet (MSDS) prior to Using

this product.

FOR INDUSTRIAL USE ONLY.

Disclaimer: All information on this data sheet is based on laboratory testing and is not Intended

for design purposes.